

501 | MVSS Flammability Tester



Model T



Model S

■ APPLICATION

Safety standards with regard to flammability of interior materials of automobiles are fixed. The MVSS Flammability Tester is used to test flammability of such materials.

■ SPECIFICATIONS

Model	T	S
Dimensions of sample	W100 x L356 x H13mm or less	
Timer	Equipped	-----
Power supply	Single-phase, AC100V, 50/60Hz, 0.1kVA	-----
Dimensions	W500 x D400 x H600mm	W500 x D210 x H400mm
Weight	Approx. 20kg	Approx. 13kg
Related standard	JIS D 1201	

Note:

1) Gas to be used (to be prepared by customer):

As a rule, a calorific value of about 38 MJ/m^3 (e.g., natural gas) should be used.

LP gas is incompatible because it has approximately twice the calorific value.

2) For Model S, please prepare a device (stopwatch, etc.) capable of measuring for approximately 15 seconds.

3) Thermometer is not provided.

Specifications are subject to change without notice.



TOYO SEIKI SEISAKU-SHO, LTD.

5-15-4, Takinogawa, Kita-ku, Tokyo 114-8557, Japan

Tel: +81-3-3916-8183 Fax: +81-3-3916-8173

www.toyoseiki.co.jp

20240903 MN (2019.03 JP)